



PhilGEPS

Philippine Government Electronic Procurement System

Central Portal for
Philippine Government
Procurement Opportunities

[Help](#)

Bid Notice Abstract

Request for Quotation (RFQ)

Reference Number 6712064
 Procuring Entity OFFICE OF THE PRESIDENT
 Title RFQ / PR 19-10-1058 / PROCUREMENT OF MATERIALS FOR OP-DIGITIZATION PROJECT
 Area of Delivery Metro Manila

Solicitation Number:	19-10-1058	Status	Pending
Trade Agreement:	Implementing Rules and Regulations	Associated Components	1
Procurement Mode:	Negotiated Procurement - Small Value Procurement (Sec. 53.9)	Bid Supplements	0
Classification:	Goods	Document Request List	0
Category:	Information Technology Parts & Accessories & Perip	Date Published	30/11/2019
Approved Budget for the Contract:	PHP 148,620.00	Last Updated / Time	29/11/2019 09:44 AM
Delivery Period:	30 Day/s	Closing Date / Time	06/12/2019 17:00 PM
Client Agency:			
Contact Person:	Patricia Kaye Lorio Amate Presidential Staff Officer I Procurement Unit, Rm 123 Mabini Hall Bldg., J.P. L Malacañang Complex, San Miguel Manila Manila Metro Manila Philippines 1005 63-2-7844286 Ext.4601 63-2-7844286 procurement_unit@malacanang.gov.ph		

Description

A) REQUEST FOR QUOTATION

1. 2 units FLATBED DOCUMENT SCANNER

Scan Function:
 Sensor Type: CIS
 Optical Resolution: 1,200 x 1,200 dp
 Output Resolution: 50 - 1,200 dpi (in 1 dpi increments)
 Scanner Bit Depth (Colour): 30-bit input, 24-bit output
 Scanner Bit Depth (Grayscale): 10-bit input, 8-bit output
 Scanner Bit Depth (Black & White): 10-bit input, 1-bit output
 Max Document Size: 216 x 297 mm
 Output File Formats: JPEG, TIFF, Multi-TIFF, PDF, Searchable PDF, BMP, PNG
 Document Capture Pro (Win): JPEG, BMP, PDF, Searchable PDF, TIFF, Multi-TIFF, PNG, DOCX, XLSX, PPTX

Scan Speed:
 Flatbed (Black / Colour): 200 dpi: 6.0 sec / 7.0 sec
 300 dpi: 6.0 sec / 7.0 sec
 600 dpi: 14 sec / 26 sec
 ADF Monochrome (Simplex/Duplex): 200dpi:25ppm /10ipm
 300 dpi: 25ppm / 10ipm
 600 dpi: 10ppm / 6.0ipm
 ADF Colour (Simplex / Duplex): 200, dpi: 25ppm / 10ipm
 300 dpi: 25ppm / 10ipm
 600 dpi: 10ppm / 6.0ipm

ADF Specifications:
 Scanner Type: sheet-fed , 3-pass duplex scanner
 Optical Sensor: CIS
 Light Source: RGB LED
 Optical Resolution: 600 dpi x 600 dpi
 Output Resolution: 50 - 1,200 dpi (in 1 dpi increments)
 Min Document Size: 89 x 127 mm (Simplex)
 89 x 170 mm (Duplex)
 Max Document Size: 215.9 x 3,048 mm
 Support Paper Thickness: 50 gsm - 120 gsm
 ADF Capacity: 50 sheets
 Automatic Duplex Scanning: Yes (3-pass)
 Daily Duty Cycle: up to 1,500 pages / day

Connectivity:
 Standard: USB 3.0
 Network: Ethernet with Optional Network Interface Unit

Supported OS and Applications:
 Supported OS: Windows XP / Vista / 7 / 8 / 8.1 / 10
 Windows Server 2003 / 2008 / 2012
 Mac OS X 10.6.8 or later
 Scanner Driver Compatibility: TWAIN, ISIS, SANE, WIA, ICA
 Bundled Applications: ISIS Driver (Web Download), Document Capture Pro (Win), Document Capture (Mac)

Power:
 Related Voltage: AC 100-220V

2. 1 unit DOCUMENT CAMERA

Main Parts Specification:

Sensor: Pick-Up Device; CMOS

Size: 1 / 2.7"

Effective Pixels; 2M Pixels (1920 x 1080)

Frame Rate; Up to 30fps

Native Resolution; 1080p (16:9 Aspect Ratio)

Video Output: Display Out; SXGA (1280 x 1024) /

XGA (1024 x 768) / WXGA (1280 x 800) /

HD (1360 x 768) / 1080p (1920 x 1080)

HDMI; 480p / 720p / 1080p

USB-B; VGA/SVGA / XGA / SXGA / WXGA / 720p / 1080p

Optical Systems:

Lens: Type; Optical Zoom / Focus

F-Number; F = 3.4 - 5

Shooting Area; Max 297 x 526 mm at 1080p output resolution

Zoom; Up to 10x Digital, Up to 12x Optical

Focus; Automatic (need to press "Focus" button)

Focus adjust time: less than 2 sec

Illumination: Upper; White LED x 2 (variable LED light)

Interface Port:

Input: D-Sub 15Pin (VGA); 1 (Black)

Output: D-Sub 15Pin (VGA); 1 (Blue)

HDMI; 1 (in common with CEC control)

USB I/O; Type B x 1

Internal Microphone; Yes (Monoral)

Memory I/O SD Card; 1 (SD / SDHC, No SDXC support)

Basic Function:

Freeze: Yes

Output Source Select: Yes

Image Brightness Adjustment: Yes

Light Brightness Control: Yes

Auto Detect Aspect Ratio: Yes

Extended Function:

Still Image Capture: Yes (need external SD card)

Video Capture: Yes (w/Audio) (need external SD card)

Digital Scroll / Pan / Tilt: Yes (available for over 2x digital zoom) (without Zoom window)

Image File Play / Slideshow: Yes (need external SD card)

Split Screen: Yes

Adjustment Function:

Image: White Balance; Yes (Auto, Cloudy, Daylight, Fluorescent, Incandescent)

Focus Lock; Yes

Image Mode; Yes (Normal, Text, Display)

Colour / B&W / Negative; Yes (Colour, Black & White, Negative)

Image Rotation; Yes (0, 180 degrees)

Noise Reduction; Yes

Microscope; Yes

Focus; Yes (Manual adjustment)

Function: HDMI Output; Yes [Auto, SDTV (480p), HDTV (720p), HDTV (1080p)]

Output Resolution; Yes [Auto, XGA (1024 x 768), WXGA (1280 x 800), WXGA (1360 x 768), SXGA (1280 x 1024),

Full HD (1920 x 1080)]

Flicker Reduction; Yes (50Hz, 60Hz)

Language; Yes

Sleep Mode; Yes

HDMI Link; Yes (On / Off)

Sleep Mode Timer; Yes

Power:

Power Supply Voltage: 100 - 240V AC (50/60 Hz)

Output Voltage of AC Power Adapter: 12V

3. 1 unit WIRELESS LCD PROJECTOR**Projection Technology:**

Projection Technology: RGB liquid crystal shutter projection system

Brightness*2:

White Light Output (Normal): 3,200lm

Colour Light Output: Normal / Eco: 3,200lm / 1,900lm

Connectivity:

Network: Wireless LAN; In-built

Analog Input: D-Sub 15 pin; 1(Blue) Composite; RCA x 1

Digital Input: HDMI; 1(MHL)

Audio Input: Stereo Mini Jack: 1

Others: USB Type A: 1 (for USB Memory, USB Document Camera, Firmware Update)

USB Type B: 1 (for USB Display, mouse, K/B/, Control, Firmware Update)

Contrast Ratio:

Auto Iris:10,000:1

Wireless Specifications:

Supported Speed for Each Mode: IEEE 802.11b: 11Mbps

IEEE 802.11g: 54Mbps

IEEE 802.11n: 130 Mbps

Wireless LAN Security: Quick Mode: WPA2-PSK

Advanced Mode: WPA2-PSK,WPA/WPA2-PSK,WPA2-EAP

Supported EAP type: PEAP, PEAP-TLS, EAP-TLS, EAP-Fast, LEAP

Supported Connection Mode: Infrastructure, Access Point

Screen Size (Projected Distance):

Standard Size: 60" screen 1.35 - 1.62m

Zoom: Wide: 30" - 300" (0.67 - 6.81m)

Zoom: Tele: 30" - 300" (0.80 - 8.18m)

Operating Temperature:

Operating Temperature: 5°C - 40°C < 41°F - 104°F> (0 m / 0 ft to 2,286m / 7,500ft) 5°C - 35°C < 41°F - 95°F> (over 2,286m / 7,500ft) (20% - 80% humidity, No condensation)

Operating Altitude:

Operating Altitude: 0m - 3,000m (0ft - 9,843 ft) (over 1,500m / 4,921ft: with high altitude mode)

Start-Up Period:

Start-Up Period: About 7.2 seconds, Warm-up period: 30 seconds

Cool Down Period:

Cool Down Period: Instant off

Internal Speaker(s):

Sound Output: Monaural: 1W X 1

Direct Power On/Off:
Direct Power On/Off: Yes/Yes

Fan Noise:
Fan Noise (Normal / Eco): 39 dB / 30dB

Wireless Specifications (Miracast):
Supported Speed for Each Mode: IEEE 802.11g (2.4GHz): 54Mbps
IEEE 802.11n (2.4GHz): 130.0 Mbps
IEEE 802.11a (5GHz): 54 Mbps
IEEE 802.11n (5GHz): 270.0 Mbps
IEEE 802.11ac (5GHz): 780 Mbps
Supported Connection Mode: Wi-Fi Direct

4. 1 unit WIRELESS PORTABLE SCANNER

Scan Function:
Scanner Type: sheet-fed colour scanner
Sensor Type: Contact Image Sensor (CIS)
Scanning Method: Fixed document and moving carriage
Light Source: RGB LED
Optical Resolution: 600 x 600 dpi
Output Resolution: 50 - 1,200 dpi (in 1 dpi increments)
Scanner Bit Depth (Colour): 48-bit input, 24-bit output
Scanner Bit Depth (Grayscale): 16-bit input, 8-bit output
Scanner Bit Depth (Black & White): 16-bit input, 1-bit output
Min Document Size: 50.8 x 50.8 mm
Max Document Size: 216 x 1,828.8 mm
Supported Paper Weight: 35 - 270 g/m2
ADF Capacity: 1 sheet
Daily Scan Volume: Up to 300 sheets / day
Interface: USB 2.0 (Micro-B), Wi-Fi

Scan Speed:
Resolution (Colour / Monochrome): 200dpi: 4.0sec (Battery) / 5.5sec (USB Bus powered)
300dpi: 4.0sec (Battery) / 5.5sec (USB Bus powered)
600dpi: 9.0sec (Battery) / 9.0sec (USB Bus powered)

Supported OS and Applications:
Supported OS: Windows XP / Vista / 7 / 8 / 8.1 / 10 / Server 2003 / Server 2008 / Server 2012 / Server 2016 Mac OS X 10.6.8 or later
File Format: JPEG, PDF, Searchable PDF, DOCX, XLSX, PPTX*3

Control Panel:
Control Panel: LCD Screen

Environmental Conditions:
Temperature: Operating: 5 - 35 °C Storage: -25 - 60 °C
Humidity: Operating: 10 - 85% (No condensation)
Storage: 10 - 90% (No condensation)

NOTE:
STANDARD WARRANTY: 1 YEAR
DELIVERY PERIOD: 30 CALENDAR DAYS

B) USE COMPANY LETTERHEAD FOR YOUR QUOTATION & ADDRESS TO:

DIR. JAMES JUPER B. AGUILAR
Head, Procurement Unit
Office of the President
M-123 Mabini Hall, J.P. Laurel St.,
Malacañang Complex,
San Miguel, Manila

Tel Number: (02) 784-4286 loc. 4601
Fax Number: (02) 784-4286 local 4709
Email Address:
procurement_unit@malacanang.gov.ph

C) ELIGIBILITY DOCUMENTS MUST BE ATTACHED TO THE QUOTATION

1. Latest/updated/valid PhilGEPS Registration Certificate
2. Latest/valid Mayor's Permit
3. Income / Business Tax
4. Omnibus Sworn Statement (Original Copy- Upon Award)

Note:
•Kindly Attach the Complete Eligibility Documents to Avoid DISQUALIFICATION.
•Include the BACK PAGE OF THE MAYOR'S/BUSINESS PERMIT if Available
•Scan the Documents in a manner that the entries are legible/readable.

D) INDICATE IN YOUR QUOTATION THE FOLLOWING

1. Terms of Payment:
2. Warranty:
3. Place of Delivery:
4. Delivery Period:
5. Price Validity Period:
6. Stock Availability:
7. Certificate of Exclusive Distributorship, if any
8. Brand
9. TIN

Created by Patricia Kaye Lorio Amate

Date Created 29/11/2019

The PhilGEPS team is not responsible for any typographical errors or misinformation presented in the system. PhilGEPS only displays information provided for by its clients, and any queries regarding the postings should be directed to the contact person/s of the concerned party.